

| L Number | Hits | Search Text | DB | Time stamp |
|----------|------|--|--------------------------------|------------------|
| 6 | 0 | (worm\$3 near2 (light or lamp)) and (game\$2 near2 boy) | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:50 |
| 11 | 0 | (worm\$3 near2 (light or lamp)) and (game\$2 near2 boy or gameboy) | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:51 |
| 16 | 0 | (worm\$3 near2 (light or lamp)) and USB | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:51 |
| 1 | 63 | worm\$3 near2 (light or lamp) | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:57 |
| 21 | 692 | (snake or fly) near2 (light or lamp) | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:58 |
| 26 | 0 | ((snake or fly) near2 (light or lamp)) and USB | USPAT; EPO; JPO; DERWENT | 2002/03/26 15:58 |
| 31 | 137 | ((snake or fly) near2 (light or lamp)) and (computer or game) | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:07 |
| 36 | 60 | ((worm\$3 near2 (light or lamp)) or ((snake or fly) near2 (light or lamp))) same connect\$3 | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:16 |
| 41 | 0 | (((worm\$3 near2 (light or lamp)) or ((snake or fly) near2 (light or lamp))) same connect\$3) and usb | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:16 |
| 46 | 1 | nyko.AS. | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:20 |
| 51 | 1 | nyko.ASN. | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:20 |
| 56 | 0 | (fly\$3 near1 light).ASN. | USPAT; EPO; JPO; DERWENT | 2002/03/26 16:20 |



| | |
|---------------|---|
| US 5666265 A | Portable workstation housing for storing and operating portable computer - has frictional c |
| US 6337162 B1 | Method of exposure, 430/5 430/17; 430/22; 430/30 |
| US 6328215 B1 | Method and system for 235/472.0 235/462.01 |
| US 6319093 B1 | Chemical-mechanical 451/6 451/41 |
| US 6290132 B1 | Holographic-based beam 235/462.3 235/472.01 |
| US 6271924 B1 | Noncontact acoustic c 356/489 356/495 |
| US 6259975 B1 | Flight control system 1701/3 244/175; 244/75R; 244/76R; 342/33; 701/14; 701/16 |
| US 6259565 B1 | Display apparatus 359/630 248/917; 345/32; 345/7; 345/8; 348/121; 348/46; 35 |
| US 6252252 B1 | Optical semiconductor 257/81 257/433; 257/436; 257/80; 257/82; 438/116 |
| US 6243207 B1 | Display apparatus 359/630 248/917; 345/32; 345/7; 345/8; 348/121; 348/46; 35 |
| US 6239559 B1 | Light source using die 315/307 315/111.21; 315/219; 315/276; 315/57 |
| US 6238851 B1 | Exposure method 430/394 355/77; 430/22; 430/30; 430/311 |
| US 6224183 B1 | Ink-jet printing apparatus 347/19 |
| US 6215587 B1 | Microscope imaging in 359/368 359/385; 359/396; 359/559 |
| US 6212817 B1 | Fly pattern, fabrication 43/42.25 43/42.27; 43/42.53 |
| US 6204913 B1 | Photographic process 355/67 355/71 |
| US 6199759 B1 | Bar code symbol scanner 235/472.0 235/462.25 |
| US 6185018 B1 | Holographic stereogram 359/23 359/22; 359/28; 359/30; 359/34 |
| US 6164837 A | Integrated microelectronic 385/90 385/88; 385/89; 385/91; 385/92 |
| US 6158659 A | Holographic laser scanner 235/462.0 235/472.01 |
| US 6117673 A | RDGB proteins and receptors 435/320.1 435/252.3; 435/69.1; 530/350; 536/23.1; 536/23.5 |
| US 6115107 A | Exposure apparatus 355/68 355/53; 355/67 |
| US 6112990 A | Compact holographic 235/462.0 235/462.25 |
| US 6108576 A | Time-resolved diffraction 600/476 600/310; 600/473 |
| US 6106821 A | Fly attractant composition 424/84 424/405; 424/43; 424/664; 424/710; 424/716; 424/71 |
| US 6091983 A | Imaging of objects in 600/431 250/341.3; 356/364; 356/433; 600/475; 600/477 |
| US 6085980 A | Holographic laser scanner 235/462.2 235/472.02 |
| US 6085978 A | Holographic laser scanner 235/462.0 235/472.01 |
| US 6076736 A | Holographic laser scanner 235/472.0 235/462.01 |
| US 6073846 A | Holographic laser scanner 235/462.0 235/462.25 |
| US 6072561 A | Exposure method and 355/53 355/55; 355/71 |
| US 6062479 A | Holographic laser scanner 235/472.0 235/462.25; 235/462.34 |
| US 6057129 A | Clock gene and method 435/69.1 435/320.1; 536/23.1; 536/23.2; 536/23.5 |
| US 6057125 A | Clock gene and gene 435/69.1 435/252.3; 435/320.1; 435/325; 514/44; 536/23.1; 53 |
| US 6025944 A | Wavelength division 359/136 359/123; 359/124 |
| US 6024282 A | Holographic laser scanner 235/462.0 235/472.01; 359/17 |
| US 6006993 A | Holographic laser scanner 235/462.2 235/462.01; 359/17 |
| US 6003772 A | Holographic laser scanner 235/462.0 235/472.01 |
| US 5985495 A | Methods for measuring 430/22 430/30 |
| US 5984185 A | Laser scanning system 235/457 235/472.02 |
| US 5982476 A | Process of forming pattern 355/67 355/47; 355/53 |
| US 5975419 A | Holographic laser scanner 235/472.0 235/462.34 |
| US 5955721 A | Holographic scanning 235/462.0 235/472.01 |
| US 5936711 A | Projection exposure 355/55 250/548; 355/53; 356/401 |
| US 5931789 A | Time-resolved diffraction 600/473 356/432; 600/310; 600/476 |
| US 5917646 A | Rotatable lens transmission 359/296 359/298; 359/299; 359/316; 359/321 |
| US 5915649 A | Roadable helicopter 244/7A 244/17.17; 244/2; 701/23 |
| US 5890441 A | Horizontal and vertical 244/12.3 244/12.1; 244/23B |
| US 5874241 A | Clock gene and gene 435/69.1 435/252.3; 435/320.1; 435/325; 514/44; 536/23.1; 53 |
| US 5870190 A | Particle sensor and receiver 356/336 356/339 |
| US 5828566 A | Vision assisted fixture 700/59 |
| US 5823468 A | Hybrid aircraft 244/2 244/12.3; 244/125; 244/209; 244/23B; 244/25; 244/2 |

LBI

| | | | |
|--------------|------------------------------------|-----------------------|--|
| US 5815306 A | Eggcrate substrate for | 359/296 | 345/107; 345/84; 345/85 |
| US 5813988 A | Time-resolved diffusive | 600/476 | 356/432; 356/446; 600/473 |
| US 5809220 A | Fault tolerant distributed | 714/12 | 714/55 |
| US 5799656 A | Optical imaging of birefringent | 600/473 | 250/341.1; 250/358.1; 600/476 |
| US 5796935 A | Voting node for a distributed | 714/11 | 714/797 |
| US 5796498 A | Holographic imaging | 359/4 | 359/24; 359/7 |
| US 5795621 A | Methods for production of | 427/180 | 427/198; 427/201; 427/294 |
| US 5777782 A | Auxiliary optics for a hybrid | 359/296 | 345/107; 349/117; 427/214 |
| US 5771114 A | Optical interface with a | 359/171 | 250/227.15; 359/110 |
| US 5757505 A | Exposure apparatus | 356/400 | 356/401 |
| US 5721677 A | Vision assisted fixture | 700/61 | 29/407.1; 700/259 |
| US 5719399 A | Imaging and characterization | 250/341.3 | 600/407; 600/473 |
| US 5715037 A | Scanning exposure apparatus | 355/53 | 250/548; 355/46; 356/401 |
| US 5710429 A | Ultrafast optical imaging | 250/358.1 | 250/330; 250/341.1 |
| US 5709245 A | Optically controlled acoustic | 137/625.6 | 137/625.62; 251/129.04 |
| US 5706278 A | Deterministic network | 370/222 | 370/443; 370/452; 370/460 |
| US 5696673 A | Vision assisted fixture | 700/66 | 700/259; 700/279; 901/47 |
| US 5691541 A | Maskless, reticle-free, projection | 250/492.1 | 355/53; 378/34 |
| US 5678351 A | Device for casting semiconductor | 43/43.1 | 43/43.14; 43/43.15 |
| US 5677757 A | Projection exposure apparatus | 355/71 | 355/53 |
| US 5676551 A | Method and apparatus for | 434/236 | 434/322; 434/323 |
| US 5675401 A | Illuminating arrangement | 355/67 | 355/53; 355/71 |
| US 5672380 A | Method for production of | 427/180 | 427/198; 427/201; 427/350 |
| US 5666265 A | Portable workstation for | 361/683 | 206/320 |
| US 5664785 A | Airplane game | 273/442 | 472/9 |
| US 5644579 A | Bi-directional data transfer | 714/726 | 714/25; 714/724 |
| US 5631773 A | Image projection method | 359/562 | 355/53; 355/67; 359/558; 359/619 |
| US 5615108 A | Vision assisted fixture | 700/59 | 901/47 |
| US 5581075 A | Multi-beam scanning | 250/205 | 250/548; 355/69; 356/400 |
| US 5555135 A | Illumination system | 359/851 | 359/857; 359/858; 362/298; 362/346 |
| US 5467942 A | Temperature sensing | 244/75R | 244/3.17; 359/169; 359/170 |
| US 5455765 A | Vision assisted fixture | 700/62 | 29/407.04; 700/259; 901/47 |
| US 5446991 A | Fishing lure with buoy | 43/42.37 | 43/42.25 |
| US 5429676 A | Apparatus for simultaneous | 118/310 | 118/323; 222/132 |
| US 5428366 A | Field sequential color | 345/102 | 345/88; 348/59 |
| US 5424552 A | Projection exposing apparatus | 250/548 | 355/53; 355/55; 356/401 |
| US 5422477 A | High accuracy optical | 250/227.1; 250/227.21 | |
| US 5410345 A | Stroboscopic illumination | 348/59 | 348/54; 359/475 |
| US 5389954 A | Laser process apparatus | 347/258 | 347/47 |
| US 5371368 A | Ultrafast optical imaging | 250/341.1 | 250/358.1; 600/425; 600/473 |
| US 5299054 A | Optical switch | 359/251 | 359/245; 359/254; 359/298; 359/315; 359/320; 385/1 |
| US 5294075 A | High accuracy optical | 244/75R | 244/3.17; 359/169; 359/170 |
| US 5274554 A | Multiple-voting fault detection | 701/33 | 244/76R; 318/564; 714/43 |
| US 5267143 A | Vision assisted fixture | 700/56 | 348/95; 700/259; 700/302; 901/47 |
| US 5255880 A | Fly by wire/fly by light | 244/197 | 244/175; 244/196 |
| US 5223776 A | Six-degree virtual pivot | 318/568.1 | 200/5R; 318/563; 318/590; 338/128; 700/17; 74/471 |
| US 5210703 A | Apparatus and method for | 359/179 | 359/178; 714/736 |
| US 5209429 A | Helicopter with retractable | 244/17.11 | 244/7R; 416/142 |
| US 5197697 A | Fly by wire/fly by light | 244/197 | 701/11 |
| US 5196746 A | Generator auxiliary for | 310/54 | 310/58; 310/59 |
| US 5182449 A | System and method for | 250/227.1 | 73/800 |
| US 5179368 A | Method and apparatus for | 345/156 | 345/180 |

L31

| | | |
|-----------------|---|--|
| US 5176385 A | Trout country competi | 273/244 |
| US 5065541 A | Artificial fishing lures | 43/42.29 43/42.24; 43/42.25; 43/44.2 |
| US 5060889 A | Apparatus and metho | 244/183 244/184; 701/16 |
| US 5039037 A | Throttle control syste | 244/234 244/175; 244/192; 244/194 |
| US 5036469 A | Pitch attitude commar | 701/16 244/181; 244/183; 701/4; 73/178T |
| US 5029778 A | Throttle control syste | 244/234 244/175; 244/220; 74/491 |
| US 5007699 A | Fiber optic reflective t | 385/46 359/173; 385/22 |
| US 5007194 A | Artificial fishing lures | 43/42.29 43/42.24; 43/42.25 |
| US 4982918 A | Force sensitive aircrai | 244/223 244/220; 244/221; 244/228 |
| US 4962448 A | Virtual pivot handcont | 700/17 200/6A; 338/128; 74/471XY |
| US 4956780 A | Flight path angle com | 701/16 244/181; 244/183; 244/186; 701/8 |
| US 4948218 A | Optoelectronic device | 359/173 359/184; 385/24 |
| US 4859913 A | Vacuum fluorescent p | 315/169.4 347/122; 430/31 |
| US 4851905 A | Vision target fixture cc | 348/169 348/86; 901/47 |
| US 4791750 A | Fishing lure with interr | 43/42.31 |
| US 4727247 A | Light attenuation sens | 250/361R 250/227.23; 250/577; 250/900 |
| US 4578615 A | Vacuum fluorescent p | 313/497 313/110; 345/32; 359/619; 445/24 |
| US 4563613 A | Gated grid structure fr | 313/497 313/422; 313/495 |
| US 4558255 A | Edge-out matrix light l | 313/497 250/227.2; 250/227.28; 313/422; 313/495; 385/120 |
| US 4530271 A | Electric actuator syste | 91/509 91/437; 92/136 |
| US 4463605 A | Simulator circuit for el | 73/866.4 434/31 |
| US 4420808 A | Multi-axis force stick, | 701/4 244/177; 244/223; 700/41; 73/862.05 |
| US 4317119 A | Stand alone collision : | 342/455 |
| US RE30845 E | Apparatus for automa | 356/440 356/409 |
| US 4195838 A | Electronic game with | 463/3 |
| US 4179021 A | Lift device arrangeme | 198/341.0; 198/346 |
| US 3829221 A | APPARATUS FOR AI | 356/440 356/409 |
| US 3740891 A | COMBINED FISHING | 43/42.02 43/42.15 |
| US 3719337 A | FLIGHT CONTROL A | 244/177 318/584; 73/178R; 73/182 |
| US 3612641 A | HOLOGRAPHIC DAT | 359/11 250/550; 359/21; 365/125; 365/216 |
| JP 080203 A, B2 | DIGITAL FLIGHT CONTROL SYSTEM | |
| US 5255880 A | Fly by wire/fly by light control system for aircraft - modifies autopilot command to control s | |
| US 5197697 A | Aircraft fly-by-wire, fly-by-light control system with manual override - allows pilot to modify | |

L31

| | | | |
|-----------------|---|-----------------------|---|
| US 6265969 B1 | Telescoping warning | 340/468 | 340/488; 340/489; 340/907 |
| US 6362572 B1 | Decorative lamp asse | 313/637 | 313/485; 313/573; 313/643 |
| US 6252252 B1 | Optical semiconducto | 257/81 | 257/433; 257/436; 257/80; 257/82; 438/116 |
| US 6115107 A | Exposure apparatus | 355/68 | 355/53; 355/67 |
| US 6091983 A | Imaging of objects in | 1600/431 | 250/341.3; 356/364; 356/433; 600/475; 600/477 |
| US 6023528 A | Non-edit multiple ima | 382/181 | |
| US 5926565 A | Computer method for | 382/181 | |
| US 5915649 A | Roadable helicopter | 244/7A | 244/17.17; 244/2; 701/23 |
| US 5911502 A | Vehicle headlight havi | 362/508 | 362/286; 362/288; 362/526 |
| US 5875263 A | Non-edit multiple ima | 382/181 | |
| US 5809220 A | Fault tolerant distribut | 714/12 | 714/55 |
| US 5742042 A | Bar code reader havir | 235/462.36 | |
| US 5664785 A | Airplane game | 273/442 | 472/9 |
| US 5555671 A | Light weight fly box | 43/57.1 | 206/315.11; 206/523; 43/54.1 |
| US 5539192 A | Bar code reader mirrc | 235/462.3; 235/462.43 | |
| US 5537006 A | Power supply | 315/127 | 315/136; 315/194; 315/308; 315/362 |
| US 5532480 A | Dynamic damper for | 250/235 | 235/462.38; 359/213 |
| US 5532468 A | Bar code reader for sr | 235/462.3; 235/462.43 | |
| US 5512744 A | Tapered beam folded | 250/234 | 235/462.36; 235/462.43; 359/221 |
| US 5508735 A | Underdeck inspection | 348/82 | 348/211 |
| US 5508503 A | Bar code reader inclu | 235/462.36 | |
| US 5495277 A | Image sensor having | 347/171 | 250/208.1; 358/296; 358/471; 358/472 |
| US 5484995 A | Pulse drive circuit for | 235/462.3; 235/462.43 | |
| US 5473150 A | Bar code reader with | 235/462.3; 235/462.43 | |
| US 5464976 A | Bar code reader havir | 235/462.1 | 235/462.36; 359/213 |
| US 5356329 A | Light display drive for | 446/485 | 362/802; 446/29; 446/326; 446/396; 472/102 |
| US 5329336 A | Exposure method anc | 355/53 | 355/68 |
| US 5322247 A | Quad-line kite | 244/153R | 244/155A; D12/321 |
| US 5007699 A | Fiber optic reflective ti | 385/46 | 359/173; 385/22 |
| US 4994716 A | Circuit arrangement fr | 315/200R | 315/241R; 315/291; 315/DIG.4; 315/DIG.7 |
| US 4982918 A | Force sensitive aircra | 244/223 | 244/220; 244/221; 244/228 |
| US 4973850 A | Variable incident angl | 250/492.1 | 250/504R |
| US 4594531 A | Circuit arrangement fr | 315/307 | 315/224; 315/287; 315/DIG.7 |
| US 4534127 A | Device for a casting fl | 43/41.2 | 43/43.11 |
| US 4501088 A | Fly trap with disposab | 43/118 | 43/122 |
| US 4493161 A | Trap for flying insects | 43/107 | 43/113; 43/122 |
| US 4464969 A | Speed governor for m | 84/95.1 | 984/204; 984/DIG.1 |
| US 4458573 A | Speed governor for m | 84/95.1 | 984/204; 984/DIG.1 |
| US 4356656 A | Flying insect killer anc | 43/113 | 43/132.1 |
| US 4253046 A | Variable intensity conl | 315/224 | 315/105; 315/276; 315/307; 315/335; 315/DIG.7 |
| US 4251945 A | Flying insect killer anc | 43/113 | 43/132.1 |
| US 4250652 A | Casting weight | 43/41.2 | 43/43.1; 43/43.11 |
| US 4162556 A | Process and apparatu | 15/312.1 | 134/37; 134/6; 57/301; 57/304 |
| US 4142356 A | Open-end spinning a | 57/301 | 57/304; 57/411 |
| US 4095401 A | Method and apparatu | 57/81 | |
| US 4093155 A | Steam powered tilting | 244/12.4 | 244/56; 244/60; 416/148; 416/171 |
| US 3752423 A | LIFTING AND/OR RO | 244/153R | 244/902; 446/30 |
| JP 2000309113 A | DEVICE FOR LIGHTING FLUORESCENT LAMP FOR OPTICAL FIXING AND OPTICAL | | |
| JP 11262749 A | METHOD AND APPARATUS FOR MEASURING QUANTITY OF UNBURNED CARBON | | |
| JP 59197822 A | OPTICAL ROTATION DETECTII | 250/216 | |
| US 4493161 A | Trap for flying insects | | |
| DE 3149829 A1 | Universal starship: the moon | | 244/158R; 244/159 |

L 36

| | |
|--------------|--|
| US 4356656 A | Flying insect killer and light fixture incorporating same |
| US 4251945 A | Flying insect killer and light fixture incorporating same |
| US 4250652 A | Casting weight |
| CN 1149652 A | Building member |
| EP 680794 B | Prod'n. of light alloy fly wheel - using a single moulding process requiring smaller space for |
| US 5356329 A | Rideable toy for child - has centrifugally operated light display visible through translucent |
| SU 1664228 A | Flying insect killer - has centrifugal elastic lines inside radial guide tubes on electric motor |
| SU 1620067 A | Lit fish feeder - having body made as two cones, in transparent material, with bases facing |

L36